

W200 DC UK

Mechanic Welding Regulation



Welder mechanical regulation of the welding current. Reliability, sturdiness and soundproof for all your particular needs.

Welder Parameters

Welding current A	A	40-200
Min/Max welding voltage	V	21.6 / 28.8
Welding service at 60% A	A	170

Max diameter of electrode

Rutile	mm	5
Basic	mm	5
Cellulose	mm	5

Power Specifications

Voltage	V	230/115
Frequency	Hz	50
Power factor	cos ϕ	0.9

Power

Single phase Maximum Power	kW/kVA	3.9 / 4.3
Single phase power COP	kVA	3.6

Engine specifications

Engine Brand	Honda	
Model	GX390 Recoil	
Version	50 Hz	
Engine cooling system	Air	
Displacement	cm ³	389
Aspiration	Natural	
Speed governor	Mechanical	
Prime gross power PRP	kW	6.6
Maximum gross power LTP ESP	kW	7.7
Oil capacity	l	1.1
Fuel	Petrol	
Specific fuel consumption 75% PRP	g/kWh	313
Starting system	Recoil	

Consumption

Consumption at 75% of load	l/h	2.2
Fuel tank capacity	l	6.1
Running time at 75% COP	h	2.8

Noise emission

Guaranteed noise level (LWA)	dB(A)	97
Noise level at 7 m	dB(A)	72

Dimensions and weight

Length	(L) mm	875
Width	(W) mm	620
Height	(H) mm	600
Dry weight	kg	80

Control Panel

Selector (8X2 position) allows to change welding current	Standard
2P+T CEE 230V 16A IP44	1
2P+T CEE 115V 32A IP44	1

Alternator and socket protection

Electric protection	IP 23
Socket protection	IP 44



The information is aligned with the Data file at the time of download. Printed on 01/06/2023 (ID 6601)

©2023 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package.
Specifications subject to change without notice

