HOISTMASTERS

Electric Chain Hoist & Trolley Options

- **Model: HMS**



Features:

- Motor Insulation: Class F.
- Duty Factor: 60%ED (40/20).
- Duty Classification: FEM 2M / ISO M5.
- Brake Type: DC Electromagnetic Brake.
- Overload Protection: Slipping Clutch.
- Limit Switch: Up & Down.
- Chain Container.
- Hoist Protection Grade: IP55.
- Pendant Control: 2, 4 or 6 points with Emergency Stop.
- Pendant Control Protection Grade: IP65.
- Control Voltage: 48VAC.
- 3m Height of Lift.
- Power Voltage: 3P 400AC 50Hz (Standard) ¦ 415v.

Model	Rated Load (kg)	Lifting Speed (m/min)	Lifting Motor Output (kW)	Load Chain		
				Ø (mm)	No. of Falls	
HMS0.125-01	125	2-Speed: 8/2	0.4 / 0.1	5.0	1	Price on application - contact WOLFF Onsite
HMS0.25-01	250	2-Speed: 8/2	0.4 / 0.1	5.0	1	
HMS0.5-01	500	2-Speed: 8/2	0.8 / 0.2	5.0	1	
HMS01-02	1000	2-Speed: 4/1	0.8 / 0.2	5.0	2	
HMS02-02	2000	2-Speed: 4/1	1.8 / 0.45	7.1	2	

1. Non-standard lift heights available.
2. Non-standard speeds available upon request.

Specifications are for guidance and may change without notice. Always check suitability before use.