acecube
compact dual fluid

# Model (ACC-DF-2450/250L)




The AceCube Compact Dual Fluid ACC-DF 2450/250L is designed for the safe and secure transporting and storage of various industrial lubricants and hazardous liquids worldwide.

| Specifications | Metric | US | Imperial |
|---|---|---|---|
| Capacity | 2428 Litres | 641 Gallons | 534 Gallons |
| Length | 2296 mm | 7ft 5" | 7ft 5" |
| Width | 1550 mm | 5ft 1" | 5ft 1" |
| Height | 1295 mm | 4ft 3" | 4ft 3" |
| Outer Tank Thickness | 3 mm | 11 Gauge | 11 Gauge |
| Inner Tank Thickness | 3 mm | 11 Gauge | 11 Gauge |
| Weight, Tare | 1222 kg | 2694 lbs | 2694 lbs |
| Weight, Laden | 3440 kg | 7584 lbs | 7584 lbs |
| Safe Fuel Fill Level | 2306 Litres | 609 Gallons | 507 Gallons |

## Approvals and Certifications

### UK & Europe


- ✓ CE Marked
- ✓ 110% bunded
- ✓ UN 31 A/Y Compliant Design
- ✓ Vibration Tested
- ✓ Lifting when Full

The information listed in this document is for illustration purposes only and may be subject to change without notice. Users are responsible for verifying its suitability for their needs.


# AdBlue Specification

| Specifications | Metric | US | Imperial |
|---|---|---|---|
| Capacity | 250 Litres | 66 Gallons | 55 Gallons |
| Safe AdBlue Liquid Fill Level | 238Litres | 63 Gallons | 52 Gallons |


**Note:** Inner tank is plastic & pipework for AdBlue is SS-304.





SECTION A-A




PLAN VIEW


REAR ISOMETRIC VIEW






FRONT VIEW



SIDE ELEVATION


FRONT ISOMETRIC VIEW

