acecube
versatile DEF

Model (ACV-DEF-1650L/436G)



The AceCube versatile DEF ACV-DEF-1650/436G range of transportable fluid storage tanks comes with a Stainless Steel fittings plate and has been designed to supply bulk DEF to multiple Stage V Engines at one time.

Specifications

Specifications	Metric	US	Imperial
Capacity	1637 Litres	432 Gallons	360 Gallons
Length	2613 mm	8ft 6"	8ft 6"
Width	1179 mm	3ft 10"	3ft 10"
Height	1295 mm	4ft 3"	4ft 3"
Outer Tank Thickness	3 mm	11 Gauge	11 Gauge
Inner Tank Thickness	15 mm	9/16"	9/16"
Weight, Tare	803 kg	1770 lbs	1770 lbs
Weight, Laden	2493 kg	5496 lbs	5496 lbs
Safe Liquid Fill Level	1555 Litres	411 Gallons	342 Gallons

Build Standards and Certifications

Our products comply with DyMac Globals© self-governed quality control procedures, sheet metal surface pre-treatment and coating technology adopted by market leading fabrication procedures. The ACV-DEF outer steel tank has been built to:

UK & Europe

- ✓ Lifting when Full
- ✓ Pressure Tested
- ✓ CE Marked

USA & Canada

- ✓ Lifting when Full
- ✓ Presure Tested

The information listed in this document is for illustration purposes only and may be subject to change without notice. Users are responsible for verifying its suitability for their needs.