

ASSEMBLY DETAILS			
PART NO.	DESCRIPTION	QTY.	WEIGHT (KG)
LEP-30-80.0.00.0.0.000	SALES GA LEP-30-80	1	1940


TECHNICAL SPECIFICATIONS	
NOMINAL RATED POWER	30kVA
ENERGY STORAGE CAPACITY	80kWh
OUTPUT VOLTAGE	3 PHASE 400/230V
BATTERY SYSTEM VOLTAGE	51.2 VDC
BATTERY SYSTEM CURRENT	314 Ah
INPUT	2 X CE 125A \ 3PH PLUG MC4 CONNECTOR-4 PAIR HARD WIRE CONNECT
OUTPUT	1 X CE 125A \ 3PH SOCKET 1 X CE 63A \ 3PH SOCKET 1 X CE 32A \ 3PH SOCKET 2 X CE 32A \ 1PH SOCKET 2 X CE 16A \ 1PH SOCKET
LIFT POINTS	FORKLIFT POCKETS, LIFT &DRAG SKID
OVERALL DIMENSION(LXWXH)mm	1846 x 1240 x 2322
WEIGHT(KG)	1940(Approx.)




PLAN VIEW




LEFT SIDE VIEW



FRONT VIEW



RIGHT SIDE VIEW



ISO VIEW

NOTE:
1.ALL THE DIMENSIONS IN mm. FOR DRAWING CLARITY, ONLY CRITICAL DIMENSIONS SHOWN.
UNDIMENSIONED FEATURES CAN BE OBTAINED FROM PART DATA FILES AVAILABLE UPON REQUEST.
2.REMOVE BURRS & SHARP EDGES.
3.UNLESS OTHERWISE SPECIFIED, ALL BENT FLANGES TO BE ASSUMED 90 DEGREES.
4.DO NOT MEASURE THE DRAWING,IF DOUBT ASK FOR CLARIFICATION
5.FINISH: **DO AS PER PART DRAWING, CHECK P.O FOR RAL VALUE FOR POWDER COATING /PAINTING.**

REV.	DESCRIPTION	DATE	CHECKED	APPROVED	REMARKS
-	ISSUED FOR MANUFACTURING	27-03-2026	27-03-2026	27-03-2026	

THIS DRAWING AND THE COPYRIGHT THEREIN IS THE PROPERTY OF DYMAC GLOBAL. IT MAY NOT BE COPIED WHOLLY OR IN PART AND IT MAY NOT BE LOANED OR DISCLOSED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF DYMAC GLOBAL

DyMac GLOBAL

TOLERANCES:
≤100 ± 2
≤1000 ± 3
ANG ± 0.5°

PROJECT TITLE: **LYNX ENERGY POD LEP 30-80**

SHEET TITLE: **SALES GA LEP-30-80**

PREPARED: **R.S**	DATE:	**27-03-2026**	
CHECKED: **G.R**	CUSTOMER:	**NA**	
APPROVED: **D.M**	SCALE:	**NTS**	
PART NO.: **LEP-30-80.0.00.0.0.00**	REV.:	**-**	
DWG. NO.: **DG-LEP-30-80-GA**	SHEET NO.:	**00 OF 00**	**A3**