
Setanta
Dual Fluid

Model (SDF-1450/350L)



The SDF-1450/350L tank is an elegant low-profile high-speed design. It comprises a large steel DEF insert sump tank converting the tank to a unique dual fluid tank design. It has been designed for adoptability and user optimization.

Specifications	Metric	US	Imperial
Capacity	1430 Litres	378 Gallons	315 Gallons
Length	2280 mm	7ft 5"	7ft 5"
Width	1300 mm	4ft 3"	4ft 3"
Height	1212 mm	3ft 11"	3ft 11"
Baffle Thickness	2 mm	14 Gauge	14 Gauge
Weight, Tare	870 kg	1918 lbs	1918 lbs
Weight, Laden	2399 kg	5288 lbs	5288 lbs
Safe Fuel Fill Level	1359 Litres	359 Gallons	299 Gallons

Approvals and Certifications

UK & Europe

- ✓ Adhering to ADR regulations
- ✓ UN 31 A/Y Compliant Design
- ✓ (IBC) Intermediate Bulk Containment
- ✓ Pressure Tested
- ✓ CE Marked

USA & Canada

- ✓ Adhering to ADR regulations
- ✓ UN 31 A/Y Compliant Design
- ✓ Lifting when Full
- ✓ Pressure Tested
- ✓ US DOT & TRANSPORT CANADA Approvals
- ✓ (IBC) Intermediate Bulk Containment

The information listed in this document is for illustration purposes only and may be subject to change without notice. Users are responsible for verifying its suitability for their needs.