acecube pro
Dual Fluid

Model (ACP-DF-680/120L) (180/32G)



The AceCube Pro Dual Fluid ACP-DF-680/120L tank is designed for the safe and secure transporting and storage of various industrial lubricants and hazardous liquids worldwide.

Specifications

Specifications	Metric	US	Imperial
Capacity	673 Litres	178 Gallons	148 Gallons
Length	1485 mm	4ft 10"	4ft 10"
Width	1150 mm	3ft 9"	3ft 9"
Height	1295 mm	4ft 2"	4ft 2"
Outer Tank Thickness	3 mm	11 Gauge	11 Gauge
Inner Tank Thickness	3 mm	11 Gauge	11 Gauge
Weight, Tare	623 kg	1373 lbs	1373 lbs
Weight, Laden	1308 kg	2883 lbs	2883 lbs
Safe Fuel Fill Level	639 Litres	169 Gallons	141 Gallons

Approvals and Certifications

UK & Europe

- ✓ Adhering to ADR regulations
- ✓ (IBC) Intermediate Bulk Containment
- ✓ UN 31 A/Y Compliant Design
- ✓ Lifting when Full
- ✓ Pressure Tested
- ✓ Vibration Tested
- ✓ CE Marked

USA & Canada

- ✓ Adhering to ADR regulations
- ✓ UL 142 Compliant Design
- ✓ ULCS601-14 @ S653
- ✓ UN 31 A/Y Compliant Design
- ✓ Vibration Tested
- ✓ Lifting when Full
- ✓ US DOT & TRANSPORT CANADA Approvals
- ✓ (IBC) Intermediate Bulk Containment
- ✓ Pressure Tested

The information listed in this document is for illustration purposes only and may be subject to change without notice. Users are responsible for verifying its suitability for their needs.