
SS-4055
Latch Kits



LATCH ORDERING INSTRUCTIONS

Specify latch kit stock number.
Specify capacity of hook to which latch will be assembled.
Specify hook material (carbon or alloy).

- Stainless steel construction with cadmium plated steel nuts.
- Shipped packaged and unassembled.
- Instructions included for easy field assembly.



SS-4055 LATCH KITS

Hook Size (t)			Hook ID Code	Stock No.	Weight Each (kg)	Dimensions (mm)			
Carbon	Alloy	Bronze				A	B	C	D
3/4	1	.5	D	1090027	.01	9.65	4.05	36.6	15.0
1	1-1/2	.6	F	1090045	.01	9.65	4.05	40.6	15.0
1-1/2 - 2	2 - 3	1.0 - 1.4	G / H	1090063	.01	11.9	4.85	46.7	20.8
3	4-1/2	2.0	I	1090081	.05	14.2	4.30	61.0	25.4
5	7	3.5	J	1090107	.05	14.7	5.10	75.5	30.7
7-1/2 - 10	11 - 15	5.0 - 6.5	K / L	1090125	.08	15.0	6.86	93.0	38.1
15	22	10.0	N	1090143	.18	21.1	9.90	125	48.3
20	30	-	O	1090161	.29	23.9	13.2	149	65.0
25 - 30	37 - 45	-	P / S	1090189	.51	55.5	9.90	165	97.5
40	60	-	T	1090205	.80	84.0	13.2	200	105


S-4088
Alloy Hook Latch Kits



LATCH ORDERING INSTRUCTIONS

Specify latch kit stock number.
Specify capacity of hook to which latch will be assembled.
Specify hook material (carbon or alloy).

- To be used on A-327 and A-339 Grade 8 sling hooks.
- Latch kits shipped unassembled and individually packaged with instructions.



S-4088 Alloy Hook Latch Kits

Hook Chain (mm)	Stock No.	Weight Each (kg)	Dimensions (mm)			
			A	B	C	D
6-7	1090250	.03	19.8	4.05	51.5	23.9
8-10	1090251	.06	26.2	4.85	68.5	31.8
13	1090252	.07	26.2	4.85	76.0	31.8
16	1090253	.07	26.2	4.85	82.5	31.8
19	1090254	.07	38.9	6.60	105	47.8
22	1090255	.07	38.9	6.60	118	51.0

© 2025 Kito Crosby. All Rights Reserved.