


AS-7 Bullet Style Jaw & Jaw



AS-11 Thimble & Jaw



AS-14 Thimble & Bullet



AS-7 Bullet Style Jaw & Jaw

AS-7 BULLET STYLE JAW & JAW				Dimensions (mm)							Replacement Bolt Kit Stock No.
Working Load Limit (t)	Wire Rope Size (mm)	Stock No.	Weight Each (kg)	A	B	C	D	E	F	G	
.40	3	1016604	.18	22.4	60.5	79.5	9.65	6.35	7.85	10.2	2003936
.68	6	1016611	.50	33.3	90.0	113	11.2	7.85	9.65	14.2	2003904
1.35	10	1016622	.82	41.4	103	132	14.2	12.7	11.2	20.6	2003905
2.70	13	1016631	1.72	51.0	138	179	20.6	19.1	16.0	23.9	2003906
4.50	16	1016640	3.63	63.5	197	256	28.7	25.4	22.4	39.5	2003907
7.65	19	1016649	6.58	76.0	251	314	31.8	33.3	25.4	54.0	2003943
9.00	22	1016652	18.1	102	334	425	44.5	44.5	38.1	82.5	2003959
13.5	25	1016658	18.1	102	334	425	44.5	44.5	38.1	82.5	2003959
22.5	32	1016662	38.1	127	405	527	60.5	51.0	51.0	93.5	2003935
31.5	38	1016667	38.1	127	405	527	60.5	51.0	51.0	93.5	2003935

5:1 Design Factor. Individually Proof Tested to 2 times the Working Load Limit.

AS-11 Thimble & Jaw

AS-11 THIMBLE & JAW				Dimensions (mm)							Replacement Bolt Kit Stock No.
Working Load Limit (t)	Wire Rope Size (mm)	Stock No.	Weight Each (kg)	A	B	C	D	E	F	G	
7.65	19	1017020	8.2	76.2	220	330	34.0	39.6	30.2	53.1	2018365
13.5	25	1017029	19.1	102	296	445	44.5	45.0	38.1	89.0	2018367

5:1 Design Factor. Individually Proof Tested to 2 times the Working Load Limit.

AS-14 Thimble & Bullet

AS-14 THIMBLE & BULLET				Dimensions (mm)							Replacement Bolt Kit Stock No.
Working Load Limit (t)	Wire Rope Size (mm)	Stock No.	Weight Each (kg)	A	B	C	D	E	F	G	
7.7	20	1017255	9.0	76.2	229	337	31.8	33.3	25.4	54.1	2003943
13.6	26	1017258	18.0	102	292	441	44.5	44.5	38.1	82.6	2003959

5:1 Design Factor. Individually Proof Tested to 2 times the Working Load Limit.

© 2025 Kito Crosby. All Rights Reserved.