


- Made from Quenched & Tempered, Fine Grain Alloy Steel from European Steel Mills.
- Links are individually Proof Tested to values shown, with certification.
- Proof Test with max 60% inside width fixture to prevent localized point loading per ASTM A952.
- Each link is marked with Product Identification Code (PIC) for traceability, Grade, chain size, SWE, GUNNEBO and BG/DGUV manufacturing ID (H32).
- Fatigue rated to at least 20,000 cycles at 1.5 times the Working Load Limit.
- Designed for use with chain, wire or synthetic rope. Applications with wire and synthetic rope generally require a 5:1 Design Factor.
- Fulfills or exceeds requirements in EN 1677:2008 (WLL +25%), ASTM A952/A952M-02, AS 3775:2014 and AS 3776:2015.

Grade 100 Welded Oversized Master Link MFX

Oversized, for 1- and 2-leg slings. Designed for use with CL, CLD, CG and CGD.

Stock No.	Code	WLL (t)	Proof Load (t)	For Grade 100 Chain Size (mm)		Dimensions (mm)				Weight (kg)
				For chain 1-leg	For chain 2-leg	L	E	D	Flat Thickness	
Z100921	MFX-108-10 GrabiQ V2	5.4	13.5	10	8	340	180	22	10	3.7
Z100922	MFX-1310-10 GrabiQ V2	8.2	20.5	13	10	340	180	28	13	4.6
Z100923	MFX-1613-10 GrabiQ V2	13.6	34.0	16	13	340	180	32	16	7.0
Z100924	MFX-2016-10 GrabiQ V2	20.6	51.5	20	16	340	180	40	20	9.7

5:1 Design Factor.



Master Link MF HDG with Engineered Flat

Stock No.	Code	WLL (t)		Dimensions (mm)				Weight (kg)
		EN1677-4	A-952/A952M	L	E	D	Flat Thickness	
BG14489	MF-86-8 HDG	2.0	2.5	120	60	13	6	0.36
BG14482	MF-108-8 HDG	3.2	4.0	140	80	17	8	0.76
BG14483	MF-1310-8 HDG	5.4	6.8	160	95	22	10	1.5
BG14484	MF-1613-8 HDG	8.2	10.3	275	145	28	13	3.9

5:1 Design Factor.

© 2026-2027 CMCO. All Rights Reserved.