
Coupling Link G

For use with Grade 100 or Grade 80 chain. For use with master link and eye hook.




Stock No.	Code	WLL (t)	Dimensions (mm)					Weight (kg)
			L	B	F	A	C	
Z100821	G-6-10	1.5	45	15	7	8	16	0.1
Z101358	G-7-10	2.0	56	18	9	11	22	0.2
Z100822	G-8-10	2.6	56	18	9	11	22	0.2
Z100823	G-10-10	4.0	68	25	12	13	26	0.3
Z100824	G-13-10	6.8	89	29	15	17	33	0.7
Z100825	G-16-10	10.3	106	36	19	20	40	1.4
Z101119	G-20-10	16.0	125	43	23	26	44	2.2
Z101339	G-22-10	20.0	152	50	26	28	59	3.6
Z101365	G-26-10	27.3	161	58	32	34	61	5.7
Z101666	G-32-10	40.0	200	70	38	40	77	9.5

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M-02 and AS 3776:2015.

Grab Hook GG

Clevis shortening hook. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




Stock No.	Code	WLL (t)	Dimensions (mm)		Weight (kg)
			L	B	
Z101844	GG-6-10	1.5	54	8	0.2
Z100845	GG-7-10	2.0	57	10	0.3
B14771	GG-8-10	2.6	57	10	0.4
B14772	GG-10-10	4.0	76	12	0.9
B14773	GG-13-10	6.8	97	16	1.8
B14774	GG-16-10	10.3	114	20	3.1
Z101152	GG-20-10	16.0	147	26	7.0

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook GG with Locking Pin

Clevis shortening hook with locking pin for extra safety. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




Stock No.	Code	WLL (t)	Dimensions (mm)		Weight (kg)
			L	B	
B14970	GG-6-10 LP	1.5	54	8	0.25
B14971	GG-8-10 LP	2.6	57	10	0.40
B14972	GG-10-10 LP	4.0	77	12	0.84
B14973	GG-13-10 LP	6.8	97	16	1.81
B14974	GG-16-10 LP	10.3	114	20	3.14
B14975	GG-20-10 LP	16.0	147	26	7.30

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook OG

Eye shortening hook. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.



Stock No.	Code	WLL (t)	Dimensions (mm)				Weight (kg)
			L	B	E	F	
Z101296	OG-7/8-10	2.6	65	10	17	10	0.3
Z101297	OG-10-10	4.0	85	12	20	12	0.7
Z101298	OG-13-10	6.8	104	16	26	16	1.6
Z101299	OG-16-10	10.3	131	20	32	19	2.8
Z101300	OG-20-10	16.0	167	26	41	23	6.0
Z101301	OG-22-10	20.0	187	26	46	26	8.1
Z101302	OG-26-10	27.3	228	32	55	38	13.2
Z101303	OG-32-10	40.0	229	40	50	27	20.7

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

© 2026-2027 CMCO. All Rights Reserved.