
Roller-Bearing Swivel, SKLI/SKLU

The Gunnebo Industries SKLI/SKLU is an electrically insulated, lubricated, and sealed roller bearing swivel. It is fully rotational, even at maximum load, tested to resist 1000 V, and suitable for protection of overhead cranes during welding operations on suspended loads.

The SKLI is equipped with a durable roller bearing, enabling high durability and safe use, even under severe load. It also has heavy-duty nylon insulation to decrease friction when in use. The SKLI is compatible with the entire Gunnebo Industries SK range for versatile use.





Roller-bearing Swivel SKLI/SKLU

For use with Grade 80 chain.

Stock No.	Code	WLL (t)	Dimensions (mm)		Weight (kg)
			L	D	
Z100316	SKLI-7/8-8	2.0	75	48	0.7
Z100414	SKLI-10-8	3.2	97	59	1.3
Z100415	SKLI-13-8	5.4	120	75	2.8
Z100416	SKLI-16-8	8.0	137	90	4.6
Z100417	SKLI-18/20-8	12.8	159	104	7.3
RS16520	SKLU-22-8*	15.5	160	109	9.2
RS16530	SKLU-26-8*	21.7	207	135	18.3

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.
* Uninsulated




Load Pin and Locking Collar – SKA

For use with Grade 80 chain.

Stock No.	Code	Weight (kg)
Z700674	SKA-6-8	0.01
Z323624	SKA-7/8-8	0.02
Z318024	SKA-10-8	0.04
Z303822	SKA-13-8	0.08
Z303725	SKA-16-8	0.14
Z145048	SKA-18/20-8	0.26
Z133530	SKA-22-8	0.35
Z605407	SKA-26-8	0.63
Z650554	SKA-32-8	1.05

4:1 Design Factor.



Master Link SKG (closed)

For use with Grade 80 chain. F or use with SK system.

Stock No.	Code	WLL (t)	Dimensions (mm)			Weight (kg)
			L	E	G	
Z419684	SKG-7/8-8	2.0	99	50	14	0.3
Z419781	SKG-10-8	3.2	127	66	18	0.6
Z419888	SKG-13-8	5.4	145	72	22	1.1
Z419985	SKG-16-8	8.2	175	82	25	1.5
Z420086	SKG-18/20-8	12.8	204	105	30	3.0

4:1 Design Factor. Fulfills requirements in: EN 1677:2008, ISO 8539:2009, ASTM A952/A952M and AS 3776:2015.

© 2025 Kito Crosby. All Rights Reserved.