IPU10



Universal - for lifting in any direction.

- Available in capacities of .5 thru 30 metric tons (higher Working Load Limits are available upon request).
- Wide variety of jaw openings available: 0 to 155mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Crosby IP logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Available in a variety of styles:
  - IPU10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
  - IPU10J - Larger jaw opening.
  - IPU10S - For use with stainless steel material.
  - IPU10H - For use with materials with a surface hardness to 472HV10 (450 HB).
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- Maintenance and repair kits are available.
- Minimum WLL is 5% of maximum WLL for .5t IPU10 only.
- Minimum WLL is 10% of maximum WLL for all other IPU10, IPU10J, IPU10S, IPU10H clamps.
- For use with materials with a surface hardness to 279HV10, only 5% of minimum WLL is needed.
- Temperature range -40 °C (-40 °F) to +100 °C (+212 °F)


IPU10S




Model IPU10 / IPU10J / IPU10S / IPU10H

Model	Working Load Limit (t)*	Stock No.	Weight Each (kg)	Dimensions (mm)										Maintenance Kit Stock No.
				Jaw A	B	C	D	E	F	G	H	J	K	
IPU10	0.5	2701675	1.9	0 - 16	44	130	216	40	115	42	28	-	11	2715054
IPU10	1	2701663	2.4	0 - 20	45	139	225	40	127	42	38	-	11	2715009
IPU10	2	2701677	8.5	0 - 35	78	201	368	70	188	64	55	-	16	2715063
IPU10	3	2701665	14.8	0 - 40	100	253	436	75	222	78	60	-	20	2715018
IPU10	4.5	2701667	16.0	0 - 40	100	253	436	75	227	82	65	-	20	2715018
IPU10	6	2701669	24.0	0 - 50	126	302	525	80	292	84	95	44	20	2715036
IPU10	9	2701671	29.5	0 - 50	126	325	552	80	310	94	104	44	20	2715288
IPU10	12	2701679	57.0	0 - 54	160	392	616	80	433	121	137	41	25	2715102
IPU10	16	2701683	79.0	5 - 64	180	463	736	88	492	121	153	45	25	2715108
IPU10	22.5	2701687	126.0	5 - 80	222	554	863	110	565	139	186	49	25	2715114
IPU10	30	2701691	141.0	5 - 80	222	554	868	110	580	153	186	54	30	2715120
With larger jaw opening														
IPU10J	0.5	2701647	1.9	15 - 30	45	128	209	40	128	42	32	-	11	2715054
IPU10J	1	2702463	2.5	20 - 40	55	151	221	40	141	42	41	-	11	2715012
IPU10J	3	2702465	17.3	40 - 80	115	270	432	75	277	78	67	-	20	2715021
IPU10J	4.5	2702467	18.9	40 - 80	115	270	432	75	281	82	72	-	20	2715021
IPU10J	6	2702469	26.5	50 - 100	126	302	515	80	336	84	95	44	20	2715040
IPU10J	9	2701673	30.5	50 - 100	126	325	550	80	360	94	105	44	20	2715050
IPU10J	12	2701681	65.0	54 - 108	178	438	662	80	491	121	136	41	25	2715105
IPU10J	16	2701685	85.0	64 - 128	208	521	784	88	562	121	160	45	25	2715111
IPU10J	22.5	2701689	149.0	80 - 155	255	628	938	110	660	139	196	49	25	2715117
IPU10J	30	2701693	165.0	80 - 155	255	628	942	110	660	153	196	54	30	2715123
For stainless steel - with universal hoisting eye														
IPU10S	0.5	2702275	1.9	0 - 16	44	130	216	40	115	42	28	-	11	2715234
IPU10S	1	2702263	2.4	0 - 20	45	139	225	40	127	42	38	-	11	2715243
IPU10S	2	2702277	8.5	0 - 35	78	201	368	70	188	64	55	-	16	2715252
IPU10S	3	2702265	14.8	0 - 40	100	253	436	75	222	78	60	-	20	2715253
IPU10S	4.5	2702267	16.0	0 - 40	100	253	436	75	227	82	65	-	20	2715253
IPU10S	6	2702269	24.0	0 - 50	126	302	525	80	292	84	95	44	20	2715254
IPU10S	9	2702271	29.5	0 - 50	126	325	552	80	310	94	104	44	20	2715255
For very hard materials - with universal hoisting eye														
IPU10H	0.5	2702175	1.9	0 - 16	44	130	216	40	115	42	28	-	11	2715207
IPU10H	0.75	2702163	2.4	0 - 20	45	139	225	40	127	42	38	-	11	2729552
IPU10H	1	2702177	7.6	0 - 35	78	201	368	70	188	64	55	-	16	2715216
IPU10H	2	2702165	14.8	0 - 40	100	253	436	75	222	78	60	-	20	2715225
IPU10H	3	2702167	16.0	0 - 40	100	253	436	75	227	82	65	-	20	2715225
IPU10H	4.5	2702169	24.0	0 - 50	126	302	525	80	292	84	95	44	20	2715227
IPU10H	6	2702171	29.5	0 - 50	126	325	552	70	310	94	104	44	20	2715229

Design Factor based on EN 13155 and ASME B30.20. Model IPU10R (remote control opening and closing via a cable) on request. Model IPU10W (wedge) available on request.







© 2025 Kito Crosby. All Rights Reserved.