UB-500 Series Top Swiveling Overhaul Balls



With **S320** Eye Hook



With **S1316 A SHUR-LOC®** Eye Hook



Both styles available with optional **McKissick®** Wedge Socket Assembly or S-422 **TERMINATOR** Wedge Socket



UWO 422T TERMINATOR Wedge Only

- Sizes 3.6 tonnes through 27 tonnes are available with Crosby's S1316A positive-locking SHUR-LOC® hook, which may be used for lifting personnel. Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Design Factor 4:1
- The top swivel design on the UB-500 assures the ball remains stationary if the wireline spins.
- The swivel incorporates a sealed roller thrust bearing together with a grease fitting for easy lubrication.
- Each ball can be equipped with the new McKissick® US-422T Wedge Socket which can be easily adjusted to fit various sizes of wireline by changing the wedge (ensure that correct wedge is used for selected wireline size).
- All hooks used on UB-500 Overhaul Balls (S320, S320N & S1316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).

Overhaul Ball Assembly

Optional US-422T Wedge Sockets

McKissick® UB-500 Model No.	UB-500 "E" Eye Hook Stock No.	UB-500 "S" SHUR-LOC® Stock No.	Working Load Limit (t)	Weight Each (kg)	Wireline Size (mm)	Model No.	Wedge Socket Assy. Stock No.	Weight Each (kg)	Wedge Only Stock No.	Weight Each (kg)
MB4T35E	1036000*	1036005	3.6	26.3	10	US4T	1044300	2.09	1047310	2.09
MB4T85E	1036009*	1036018	3.6	46.3	11	US4T	1044309	2.09	1047301	2.09
MB4T150E	1036027*	1036032	3.6	73.5	13	US4T	1044318	2.09	1047329	2.09
MB4T200E	1036036*	1036041	3.6	91.2	13	US5T	1044327	3.86	1047338	3.86
MB7T85E	1036045*	1036050	6.3	49.4	14	US5T	1044336	3.86	1047347	3.86
MB7T150E	1036054*	1036063	6.3	77.1	16	US5T	1044345	3.86	1047356	3.86
MB7T200E	1036072*	1036077	6.3	95.3	16	US6T	1044354	4.26	1047365	4.26
MB7T285E	1036081*	1036086	6.3	146	19	US6T	1044363	4.26	1047374	4.26
MB10T150E	1036090*	1036095	9.0	98						
MB10T200E	1036099*	1036108	9.0	118						
MB10T285E	1036117*	1036122	9.0	166	16	US6T	1044354	4.26	1047365	4.26
MB10T350E	1036126*	1036131	9.0	183	19	US6T	1044363	4.26	1047374	4.26
MB10T650E	1036135*	1036140	9.0	326	22	US8T	1044404	9.44	1047425	9.44
MB12T150E	1036144*	–	10.8	98	25	US8T	1044417	9.44	1047431	9.44
MB12T200E	1036153*	–	10.8	117	28	US10T	1044426	21.1	1047440	21.1
MB12T285E	1036171*	–	10.8	166	32	US10T	1044435	21.1	1047459	21.1
MB12T350E	1036180*	–	10.8	183						
MB12T650E	1036189*	–	10.8	326						
MB15T200E	1036198*	–	13.5	135						
MB15T350E	1036207*	–	13.5	207						
MB15T650E	1036216*	–	13.5	342						
MB15T1150E	1036225*	–	13.5	595						
MB20T200E	1036234*	–	18.0	135	16	US8AT	1044372	7.94	1047383	7.94
MB20T350E	1036243*	–	18.0	207	19	US8AT	1044381	7.94	1047392	7.94
MB20T650E	1036252*	–	18.0	342	22	US8T	1044404	9.44	1047425	9.44
MB20T1150E	1036261*	–	18.0	595	26	US8T	1044417	9.44	1047431	9.44
MB25T350E	1036270	–	22.5	242	28	US10T	1044426	21.1	1047440	21.1
MB25T650E	1036279	–	22.5	392	32	US10T	1044435	21.1	1047459	21.1
MB25T1150E	1036288	–	22.5	645						
MB30T650E	1036297	–	27.0	392						
MB30T1150E	1036306	–	27.0	645						

4:1 Design Factor. * Utilizes Crosby "N" style hooks with integrated latch. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit. Standard Crosby S-5 Thrust style swivels can not be used with UB-500 Overhaul Balls. For replacement swivels, contact Crosby Customer Service.

© 2026-2027 Kito Crosby. All Rights Reserved.