

HF-1

- Hay Fork Pulleys with Swivel Hook or Swivel Eye
- Forged steel eyes and hooks.
- Available painted or zinc plated.
- One piece pressed steel shells.
- Edges well rounded to prevent chaffing of rope.
- Can be equipped with hook latch.
- Furnished with roller bearings.
- Pressure lube fittings.
- Natural Rope: Rope constructed of natural or plant based fibers, including manila, hemp, linen, cotton, coir, jute, and sisal.



HF-2

HF-1 / HF-2 Hay Fork Pulleys with Swivel Hook or Swivel Eye

Sheave Diameter (mm)	Model No.	Hay Fork Pulleys Stock No.		Working Load Limit (t)	Wire Rope Diameter (mm)	Rope Type	End Fitting	Weight Each (kg)
		Painted	Zinc Plated					
114	HF-1	170022	170594	.91	32 MR	Natural Rope	Swivel Hook	2.72
114	HF-2	170086	170629	.91	32 MR	Natural Rope	Swivel Eye	2.72
114	HF-3	170148	170656	.91	13 WR	Wire Rope	Swivel Hook	2.72
114	HF-4	170200	170683	.91	13 WR	Wire Rope	Swivel Eye	2.72

4:1 Design Factor.



171

- Steel sheaves with roller bearings and pressure lubrication.
- Forged steel swivel eyes.
- Easy opening feature shown available in 303mm size only.

APPLICATION AND WARNING INFORMATION
SECTION 17

171 Tong Block

Sheave Diameter (mm)	Stock No.	Working Load Limit (t)	Wire Rope Diameter (mm)	Weight Each (kg)
152	171012	.45	19	4.99
203	171058	.91	19	5.44
254	171101	2.27	19	13.6
305	171156	2.27	19	15.9

4:1 Design Factor.



443

- All steel construction, steel sheaves mounted on roller bearings, grooved for maximum of 3/4" wire rope diameter.
- May be used with three parts of line if utilizing dead end becket.

443 Lay Down Block

Sheave Diameter (mm)	Stock No.	Working Load Limit (t)	Wire Rope Diameter (mm)	Weight Each (kg)
114	171414	.23	13	5.44
152	171432	.45	19	7.71

4:1 Design Factor.

© 2025 Kito Crosby. All Rights Reserved.