450MM RED PVC GAUNTLETS - PAIR

MODEL NO's: **9114, 9114/12**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

REFER TO INSTRUCTIONS

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.


1. INTRODUCTION

Fully coated PVC gloves give excellent abrasion protection for whole forearm. Wide-ranging applications, as waterproof coating repels oil, grease and non-corrosive liquids. Ideal for farm/silage use. Conforms to BS EN 388:2016 4-1-3-1-X.

2. SAFETY

- ✓ Ensure the glove is suitable for the task at hand.
- ✓ Before use, the glove shall be visually controlled. In case of deterioration the gloves must be scrapped (abrasion, cut, tear, puncture).
- × **DO NOT** wear these gloves when there is a risk of entanglement by moving parts of machines.
- ✓ For multilayer gloves that can be separated, the performance levels are only applicable to the whole glove, including all layers.

3. PERFORMANCE

Mechanical Hazard EN 388  4131X	Abrasion Resistance	4	The numbers indicate the performance level of the glove. 1 = lowest 4 = highest 5 highest for blade cut resistance. 'X' indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
	Blade Cut Resistance	1	
	Tear Resistance	3	
	Puncture Resistance	1	
	Cut Resistance	X	

4. INSTRUCTIONS FOR USE

4.1. Place glove over hand fitting the thumb and fingers in the appropriate positions making sure the glove is fitted comfortably to carry out the task at hand.

4.2. Remove by pulling the glove upward from the fingers.

5. MAINTENANCE

- ✓ The packaging provided with the glove is suitable for transport.
- ✓ Replace the gloves if worn or damaged.
- ✓ Inspect gloves for damage before wearing them.
- ✓ Wash the out side of the gloves in mild detergent only. **DO NOT** tumble dry.

6. OBSOLESCENCE

The design performance is not significantly affected by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.

ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

REGISTER YOUR PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR

01284 757500 **sales@sealey.co.uk** **www.sealey.co.uk**

© Jack Sealey Limited