
Drop Forged Turnbuckle Jaw/Jaw – TBJJ





- Drop forged, high tensile steel, SAE 1035 or SAE 1045.
- Hot dipped galvanised finish.
- Meets the performance requirements of ASTM F1145-92 (formerly US Fed. Spec. FF-T-791b).
- Temperature range -20°C up to +200°C.
- Proof load tested to 2.5 times the W.L.L.
- Minimum breaking load is 5 times the W.L.L.
- UNC Threads.
- All items available with lock nuts.
- Up to 5/8" with safety bolt, 3/4" and above with cotter pins.
- Marked with CE, W.L.L, manufacturers ID, size, traceability code and L/R.
- Certification available 2.1 DoC

Product Code	Size inches	Take Up inches	W.L.L. t	A mm	B mm	D mm	E mm	F mm	C mm	O mm	Weight kgs

Product Code	Size	Take Up	W.L.L.	A	B	D	E	F	C	O	Weight
	inches	inches	t	mm	mm	mm	mm	mm	mm	mm	kgs
TBJJ6X4	1/4	4	0.23	120	102	11.5	15.75	7.5	200	302	0.16
TBJJ8X4.5	5/16	4 1/2	0.36	138	114	12.7	21.2	7.6	244	358	0.24
TBJJ10X6	3/8	6	0.54	180	152	13.7	21.5	9	290	442	0.71
TBJJ12X6	1/2	6	1	190	152	16	26.5	11	330	482	0.37
TBJJ12X9	1/2	9	1	267	229	16	26.5	11	406	635	0.79
TBJJ12X12	1/2	12	1	343	305	16	26.5	11	480	785	1.09
TBJJ16X6	5/8	6	1.59	203	152	21	33	14	378	530	1.35
TBJJ16X9	5/8	9	1.59	279	229	21	33	14	454	683	1.53
TBJJ16X12	5/8	12	1.59	355	305	21	33	14	530	835	1.79
TBJJ19X6	3/4	6	2.36	213	152	26	37.25	17.5	422	574	1.99
TBJJ19X9	3/4	9	2.36	289	229	26	37.25	17.5	498	727	2.48
TBJJ19X12	3/4	12	2.36	365	305	26	37.25	17.5	574	879	2.68
TBJJ19X18	3/4	18	2.36	517	451	26	37.25	17.5	726	1183	3.32
TBJJ22X6	7/8	6	3.27	222	152	31	42.75	20.5	466	618	3.15
TBJJ22X12	7/8	12	3.27	374	304	31	42.75	20.5	618	922	3.96
TBJJ22X18	7/8	18	3.27	527	457	31	42.75	20.5	770	1227	5.09
TBJJ25X6	1	6	4.54	233	152	33	52	24	510	662	4.44
TBJJ25X12	1	12	4.54	385	305	33	52	24	662	967	5.69
TBJJ25X18	1	18	4.54	537	457	33	52	24	814	1271	6.74
TBJJ25X24	1	24	4.54	690	610	33	52	24	966	1576	8.03
TBJJ32X6	1 1/4	6	6.89	236	152	47	70.5	31	598	598	8.55
TBJJ32X12	1 1/4	12	6.89	388	305	47	70.5	31	750	1055	10.27
TBJJ32X18	1 1/4	18	6.89	541	457	47	70.5	31	902	1359	11.99
TBJJ32X24	1 1/4	24	6.89	693	610	47	70.5	31	1054	1664	13.69
TBJJ38X12	1 1/2	12	9.71	403	305	57	70.5	37	800	1105	13.56
TBJJ38X18	1 1/2	18	9.71	555	457	57	70.5	37	952	1409	16.2
TBJJ38X24	1 1/2	24	9.71	708	610	57	70.5	37	1104	1714	18.88
TBJJ44X18	1 3/4	18	12.7	571	457	66	85	44	1046	1503	25.15
TBJJ44X24	1 3/4	24	12.7	724	610	66	85	44	1198	1808	28.06
TBJJ50X24	2	24	16.8	740	610	66.3	92	54	1340	1950	43.71
TBJJ63X24	2 1/2	24	27.2	795	610	78	110.8	60.5	1478	2088	81.8
TBJJ70X24	2 3/4	24	34	795	610	93.5	104.5	73	1562	2172	95.14