ENG

GANTERUD L12 Pro Proven and robust technology in a new application

Radio-controlled precision levelling and handling. Maximises efficiency, reduces installation time and increases safety



GANTERUD®
Lifting Solutions

GANTERUD L12 Pro

MADE IN SWEDEN





Levelling of both light and heavy objects

The L12 Pro levelling device uses both new and proven technology to level loads efficiently and safely with a high degree of precision. The levelling equipment can handle both light and heavy objects from 0 kg up to 12 tonnes.

Turning heavier objects 90 degrees

Here, the L12 Pro can be used as a snatch block. The chain wheel is disengaged using the remote control for free-running chain with the same function as a snatch block. Longer chain packages can be ordered as an option.

Precise and comprehensive levelling

The L12 Pro has a reversible stroke length of up to 4 metres per hook and can be precision levelled at two speeds.

Increases productivity rate many times over

The L12 Pro levels the objects it is lifting easily and safely with the simple press of a button, reducing both expensive crane time and waiting times.

Strong and robust

Thanks to its robust, tried and tested technology, combined with reliable electrical operation, the L12 Pro is able to operate in temperatures ranging from -20 to +40 degrees Celsius in demanding environments.

Sturdy, durable and reliable

The sturdy casing, along with the IP65-rated electrical system, means that the L12 Pro is easy to clean.

Radio control

With its user-friendly, IP67-rated remote control, the L12 Pro is easy to operate.

Minimal service

Other than cleaning, the only thing you need to think about is charging the battery. The battery status is indicated on the levelling equipment and, with normal use, it is sufficient to charge the battery once a week.





Technical data

Lifting capacity:	Max. 12 tonnes
Load imbalance capacity:	Max. 2.5 tonnes
Max. levelling length:	4 m (2 m in both directions) in standard version.
Two levelling speeds	
Max. chain angle:	60° at 12 tonne load
Total chain length	4 m in standard version.
Chain dimensions	48x16 mm
Unloaded weight	approx. 295 kg (incl. chain and hooks)
Height	750 mm
Width	740 mm
Depth	595 mm

Control system

Radio range:	100 m unobstructed view
Voltage, electric motor:	24 VDC
Power consumption, rest:	50 mA
Power consumption, max. continuous:	24 A
Power consumption, peak	30 A

Certification

CE marked product

Environmental requirements

Operating temperature:	-20°C to +40°C
Storage temperature:	-20°C to +45°C
Relative humidity (RH):	0–90% during storage

Optional extra equipment

Protective cover
Chain kit in other lengths
Extra batteries
Transport packaging

We reserve the right to alter specifications or designs without prior notification, and make reservation for any factual errors. Variations in specifications and equipment standards may occur between different geographical markets. Please contact us for more information regarding applicable product specifications and local adaptations.

GANTERUD
Lifting Solutions

Ganterud Lifting Solutions AB
www.ganterud.se