SPILL KITS (15LTR, 30LTR OR 50LTR)

MODEL NO: **SCK15.V3, SCK30.V3 or SCK50.V3**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions | Wear eye protection | Wear protective gloves | Wear safety footwear | Wear protective clothing | Wear a mask

1. SAFETY

- ✓ Store in a dry easily accessible area.
  IMPORTANT: Make sure the kit is in a known location.
- ❑ **WARNING!** Find out the nature of the spilled substance, it may help to deal with it more effectively.
  IMPORTANT: Try to locate the source and stem the flow, put a drip tray or bucket in place.
- ✓ Be aware of the safety requirements (C.O.S.H.H.) for all stored fluids in your workshop.
- ✓ Wear safety equipment as advised in (C.O.S.H.H.) statements when using fluid or cleaning up after a spillage.
- ✓ Evacuate the area and notify anyone nearby, then get help immediately.
- ✓ Seal off area with a barrier, tape or a sign.
- ✓ Check that no-one is injured, seek medical advice.
- ✓ Mark in permanent felt tip pen the fluid contained in the “HAZARDOUS WASTE ONLY” bag.
- ✓ Dispose of hazardous waste immediately and responsibly.
- × **DO NOT** use any single item in the kit more than once.
- × **DO NOT** use the kit for any purpose other than for which it is designed.
- × **DO NOT** use whilst eating, drinking, smoking; under the influence of drugs, alcohol, intoxicating medication, or if fatigued.

Handling a Spill - Quick Guide	
1	Move away and get help
2	Make the area safe
3	Assess for injuries
4	Identify the spillage
5	Fetch the spill kit
6	Put on appropriate PPE
7	Limit contamination
8	Contain the spillage
9	Mop up the spill

2. INTRODUCTION

Designed to absorb spills and drips with a maximum capacity of 15L. Contains a range of high quality absorbents, including high-grade polypropylene pads that can absorb up to 1L of fluid and featuring a double weight cover stock for maximum absorbency. Supplied with 1.2m absorbent sock specially designed to absorb up to 5L of fluid and create barriers to keep spills from spreading. Suitable for use with oil, petrol, diesel, coolants, mild solvents, water and other spills. Full list of absorbent applications provided in each kit. Supplied in a resealable storage bag.

3. SPECIFICATION


Model No:	**SCK15.V3**	**SCK30.V3**	**SCK50.V3**
Capacity:	15L	30L	50L
Contents:	Pad (x10), Sock, Disposal Bag with Ties (x1)	Pad (x15), Sock (x3), Disposal Bag with Ties (x1)	Pad (x25), Sock (x5), Disposal Bag with Ties (x1)
Sizes:	Pad - 500 x 400mm, Sock - 80mm x 1.2mm	Pad - 500 x 400mm, Sock - 80mm x 1.2mm	Pad - 500 x 400mm, Sock - 80mm x 1.2mm

4. OPERATION

4.1. Shallow spills and final absorption of a spill should be carried out using pads, but only once containment is complete. The pads should be left in contact with the fluid for about two or three minutes, or until saturated. Each pad will contain up to one litre of fluid approximately, depending upon viscosity.

4.2. When using the absorbent sock, it should be used to form a temporary dam to contain fluid and not as a mop. A nominal 300mm overlap of ends to contain fluid is suggested. (Smaller spills would require the SCK15 kit, medium spills SCK30 kit and larger spills SCK50 kit). All sold Separately.

4.3. Included in the kit is a large clearly marked disposal bag and associated tie. All used absorbent’s should be packed in the disposal bag and the contents indelibly marked in the spaces marked “PRODUCT” and “CATEGORY”.
Dispose of immediately, following all local environmental guidelines.




SCK50.V3


© Jack Sealey Limited

Original Language Version

SCK30.V3



SCK50.V3



ENVIRONMENT PROTECTION
Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

REGISTER YOUR PURCHASE HERE

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.
IMPORTANT: No Liability is accepted for incorrect use of this product.
WARRANTY: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK
Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • **Email:** sales@sealey.co.uk • **Web:** www.sealey.co.uk

© Jack Sealey Limited