FORKLIFT ACCESS PLATFORMS

Crane Slung Safety Cage

The crane slung safety cage is a man riding basket lifted by an overhead crane, for access and maintenance where a forklift cannot reach. It is designed to BS EN 14502 for lifting persons in suspended baskets.

- ✓ Designed to BS EN 14502
- ✓ Four-legged lifting chains
- ✓ Overhead safety guards

PART NO. WOS-FA-1030



KEY FEATURES

- Step-through or gated entry
- Fork stirrups for positioning by forklift
- Mild steel construction
- CE and UKCA marked

SPECIFICATIONS

Part no.	Entry	Capacity (kg)	Entry	No Of People	Length (mm)	Width (mm)	Max No of People
WOS-FA-1030-01	Step-through rails	500	Through bars	2	1100	1500	4
WOS-FA-1030-02	Gated	500	Side gate	2	1100	1500	4

SPECIFICATIONS

Part no.	Entry	Dimensions (L x W x H) mm
WOS-FA-1030-01	Step-through rails	1100 x 1500 x 2159
WOS-FA-1030-02	Gated	1100 x 1500 x 2159

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.