JIBS

Forklift Jib - Carriage Mounted, Extending



The carriage mounted extending forklift jib turns a forklift into a dedicated lifting crane, with a beam that extends manually from 2,000 to 3,000 mm. Extend it for distant loads or retract it to manoeuvre in tight spaces.

- ✓ Carriage mounted
- ✓ Extends 2,000 to 3,000 mm
- ✓ Wide back plate reduces load swing

PART NO. WOS-FA-1108

KEY FEATURES

- Multiple lifting points
- Hook and shackle supplied
- Six models for 2,000 to 5,000 kg trucks

SPECIFICATIONS

Part no.	Option	Min Truck Capacity (kg)	Capacity at 1,000 mm (kg)	Capacity at 1,250 mm (kg)	Capacity at 1,500 mm (kg)	Capacity at 1,750 mm (kg)	Capacity at 2,250 mm (kg)
WOS-FA-1108-01	1,800 kg at 500 mm	2000	1100	900	720	580	360
WOS-FA-1108-02	2,200 kg at 500 mm	2500	1400	1100	1000	830	560
WOS-FA-1108-03	2,700 kg at 500 mm	3000	1450	1200	1100	900	670
WOS-FA-1108-04	3,100 kg at 500 mm	3500	1900	1500	1200	1000	730
WOS-FA-1108-05	3,500 kg at 500 mm	4000	2000	1600	1300	1100	820
WOS-FA-1108-06	4,400 kg at 500 mm	5000	2700	2200	1850	1400	900

SPECIFICATIONS

Part no.	Option	Capacity at 2,500 mm (kg)	Capacity at 2,750 mm (kg)	Capacity at 3,000 mm (kg)	(mm)	C of G (Min) (mm)	C of G (Max) (mm)
WOS-FA-1108-01	1,800 kg at 500 mm	330	260	210	600	666	880
WOS-FA-1108-02	2,200 kg at 500 mm	440	320	230	600	666	880
WOS-FA-1108-03	2,700 kg at 500 mm	490	360	270	600	717	930
WOS-FA-1108-04	3,100 kg at 500 mm	580	450	370	600	717	930
WOS-FA-1108-05	3,500 kg at 500 mm	670	540	460	600	717	930
WOS-FA-1108-06	4,400 kg at 500 mm	750	620	500	600	717	930

SPECIFICATIONS

Part no.	Option	Weight (kg)
WOS-FA-1108-01	1,800 kg at 500 mm	102
WOS-FA-1108-02	2,200 kg at 500 mm	102
WOS-FA-1108-03	2,700 kg at 500 mm	175
WOS-FA-1108-04	3,100 kg at 500 mm	175
WOS-FA-1108-05	3,500 kg at 500 mm	175
WOS-FA-1108-06	4,400 kg at 500 mm	175

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.

Specifications may change without notice. E&OE.