JIBS

Forklift Jib - Carriage Mounted, Hydraulic Telescopic



The carriage mounted hydraulic telescopic forklift jib extends and retracts from the cab using the truck's auxiliary hydraulics. It combines the stability of a carriage-mounted jib with reach that can be changed without anyone approaching the load.

- ✓ Hydraulic extension from the cab
- ✓ Carriage mounted
- ✓ Wide back plate reduces swing

PART NO. WOS-FA-1114

KEY FEATURES

- Multiple lifting points
- Hook and shackle supplied

SPECIFICATIONS

Part no.	Option	(mm)	C of G (Min) (mm)	C of G (Max) (mm)	Weight (kg)
WOS-FA-1114-01	1,800 kg at 500 mm	600	666	880	102
WOS-FA-1114-02	2,200 kg at 500 mm	600	666	880	102
WOS-FA-1114-03	2,700 kg at 500 mm	600	717	930	175
WOS-FA-1114-04	3,100 kg at 500 mm	600	717	930	175
WOS-FA-1114-05	3,500 kg at 500 mm	600	717	930	175

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.

Specifications may change without notice. E&OE.