JIBS

Forklift Jib - Low Profile, Fixed Beam



The low liner forklift jib is an inexpensive way to give your forklift or telehandler crane-style reach. Its low profile beam gets into restricted spaces, so it is ideal for picking up products that are hard to palletise, such as motors and press tools, from awkward positions.

- ✓ Low profile for restricted spaces
- ✓ Fixed 1,800 mm beam
- ✓ Six lifting points

PART NO. WOS-FA-1098

KEY FEATURES

- Hook and shackle supplied, movable between points
- Nine models for 1,000 to 5,000 kg trucks
- Large fork pockets with heel retaining pins
- Suits forklifts and telehandlers

SPECIFICATIONS

Part no.	Option	Min Truck Capacity (kg)	Capacity at 500 mm (kg)	Capacity at 750 mm (kg)	Capacity at 1,000 mm (kg)	Capacity at 1,250 mm (kg)	Capacity at 1,500 mm (kg)
WOS-FA-1098-01	800 kg at 500 mm	1000	800	630	500	380	310
WOS-FA-1098-02	1,000 kg at 500 mm	1300	1000	800	630	470	380
WOS-FA-1098-03	1,300 kg at 500 mm	1500	1300	900	680	500	450
WOS-FA-1098-04	1,800 kg at 500 mm	2000	1800	1400	1100	900	720
WOS-FA-1098-05	2,200 kg at 500 mm	2500	2200	1700	1400	1100	1000
WOS-FA-1098-06	2,700 kg at 500 mm	3000	2700	1900	1450	1200	1100
WOS-FA-1098-07	3,100 kg at 500 mm	3500	3100	2400	1900	1500	1200
WOS-FA-1098-08	3,500 kg at 500 mm	4000	3500	2700	2000	1600	1300
WOS-FA-1098-09	4,400 kg at 500 mm	5000	4400	3400	2700	2200	1850

SPECIFICATIONS

Part no.	Option	Capacity at 1,750 mm (kg)	Hook Height (mm)	Last Hole (mm)	Max Fork Width (mm)	Max Fork Thickness (mm)	Fork Spread (mm)
WOS-FA-1098-01	800 kg at 500 mm	230	289	1750	130	55	360
WOS-FA-1098-02	1,000 kg at 500 mm	280	289	1750	130	55	360
WOS-FA-1098-03	1,300 kg at 500 mm	380	289	1750	130	55	360
WOS-FA-1098-04	1,800 kg at 500 mm	580	339	1750	130	55	360
WOS-FA-1098-05	2,200 kg at 500 mm	830	354	1750	130	55	360
WOS-FA-1098-06	2,700 kg at 500 mm	900	354	1750	170	70	460
WOS-FA-1098-07	3,100 kg at 500 mm	1000	364	1750	170	70	460
WOS-FA-1098-08	3,500 kg at 500 mm	1100	414	1750	170	70	460
WOS-FA-1098-09	4,400 kg at 500 mm	1400	438	1750	170	70	460

SPECIFICATIONS

Part no.	Option	Weight (kg)
WOS-FA-1098-01	800 kg at 500 mm	125
WOS-FA-1098-02	1,000 kg at 500 mm	125
WOS-FA-1098-03	1,300 kg at 500 mm	125
WOS-FA-1098-04	1,800 kg at 500 mm	125
WOS-FA-1098-05	2,200 kg at 500 mm	127
WOS-FA-1098-06	2,700 kg at 500 mm	129
WOS-FA-1098-07	3,100 kg at 500 mm	129
WOS-FA-1098-08	3,500 kg at 500 mm	129
WOS-FA-1098-09	4,400 kg at 500 mm	186

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.

Specifications may change without notice. E&OE.