JIBS

Forklift Jib - Raised, Fixed Beam



The raised forklift jib is a fixed-length jib that mounts on the forks of any truck and lifts the beam above the fork line. That gives more hook height and a better view of the load. It is the ideal attachment for lifting and moving loads that are not suitable for palletising.

- ✓ Raised beam for extra hook height
- ✓ Better view of the load
- ✓ Fixed 1,800 mm beam

PART NO. WOS-FA-1099

KEY FEATURES

- Four lifting points
- Hook and shackle supplied
- Nine models for 1,000 to 5,000 kg trucks
- Large fork pockets with heel retaining pins

SPECIFICATIONS

Part no.	Option	Min Truck Capacity (kg)	Capacity at 1,000 mm (kg)	Capacity at 1,250 mm (kg)	Capacity at 1,500 mm (kg)	Capacity at 1,750 mm (kg)	(mm)
WOS-FA-1099-01	800 kg at 500 mm	1000	500	380	310	230	60
WOS-FA-1099-02	1,000 kg at 500 mm	1300	630	470	380	280	60
WOS-FA-1099-03	1,300 kg at 500 mm	1500	680	500	450	380	60
WOS-FA-1099-04	1,800 kg at 500 mm	2000	1100	900	720	580	60
WOS-FA-1099-05	2,200 kg at 500 mm	2500	1400	1100	1000	850	60
WOS-FA-1099-06	2,700 kg at 500 mm	3000	1450	1200	1100	900	80
WOS-FA-1099-07	3,100 kg at 500 mm	3500	1900	1500	1200	1000	80
WOS-FA-1099-08	3,500 kg at 500 mm	4000	2000	1600	1300	1100	80
WOS-FA-1099-09	4,400 kg at 500 mm	5000	2700	2200	1850	1400	80

SPECIFICATIONS

Part no.	Option	Max Fork Size (mm)	Fork Spread (mm)	Weight (kg)
WOS-FA-1099-01	800 kg at 500 mm	140 x 60	500	108
WOS-FA-1099-02	1,000 kg at 500 mm	140 x 60	500	108
WOS-FA-1099-03	1,300 kg at 500 mm	140 x 60	500	108
WOS-FA-1099-04	1,800 kg at 500 mm	140 x 60	500	108
WOS-FA-1099-05	2,200 kg at 500 mm	140 x 60	500	136
WOS-FA-1099-06	2,700 kg at 500 mm	180 x 80	580	136
WOS-FA-1099-07	3,100 kg at 500 mm	180 x 80	580	136
WOS-FA-1099-08	3,500 kg at 500 mm	180 x 80	580	136
WOS-FA-1099-09	4,400 kg at 500 mm	180 x 80	580	136

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.

Specifications may change without notice. E&OE.