JIBS

Forklift Jib - Raised, Hydraulic Telescopic



The hydraulic telescopic forklift jib is our raised extending jib with a hydraulic ram, so the driver extends and retracts the arm from the cab using the truck's auxiliary hydraulics. No one needs to approach the jib to change the reach.

- ✓ Hydraulic extension from the cab
- ✓ Raised beam
- ✓ Multiple lifting points

PART NO. WOS-FA-1104

KEY FEATURES

- Hook and shackle supplied
- Large fork pockets with heel retaining pins

SPECIFICATIONS

Part no.	Option	Truck Capacity (kg)	Capacity at 1,000 mm (kg)	Capacity at 1,250 mm (kg)	Capacity at 1,500 mm (kg)	Capacity at 1,750 mm (kg)	Capacity at 2,000 mm (kg)
WOS-FA-1104-01	1,800 kg at 500 mm	2000	1100	900	720	580	500
WOS-FA-1104-02	2,200 kg at 500 mm	2500	1400	1100	1000	850	750
WOS-FA-1104-03	2,700 kg at 500 mm	3000	1450	1200	1100	900	840
WOS-FA-1104-04	3,100 kg at 500 mm	3500	1900	1500	1200	1000	900
WOS-FA-1104-05	3,500 kg at 500 mm	4000	2000	1600	1300	1100	1000

SPECIFICATIONS

Part no.	Option	Capacity at 2,250 mm (kg)	Capacity at 2,500 mm (kg)	Capacity at 2,750 mm (kg)	Capacity at 3,000 mm (kg)	(mm)	Max Fork Size (mm)
WOS-FA-1104-01	1,800 kg at 500 mm	360	330	260	210	60	140 x 60
WOS-FA-1104-02	2,200 kg at 500 mm	560	440	320	230	60	140 x 60
WOS-FA-1104-03	2,700 kg at 500 mm	670	490	360	270	80	180 x 80
WOS-FA-1104-04	3,100 kg at 500 mm	730	580	450	370	80	180 x 80
WOS-FA-1104-05	3,500 kg at 500 mm	820	670	540	460	80	180 x 80

SPECIFICATIONS

Part no.	Option	Fork Spread (mm)	Weight (kg)
WOS-FA-1104-01	1,800 kg at 500 mm	500	124
WOS-FA-1104-02	2,200 kg at 500 mm	500	124
WOS-FA-1104-03	2,700 kg at 500 mm	580	202
WOS-FA-1104-04	3,100 kg at 500 mm	580	202
WOS-FA-1104-05	3,500 kg at 500 mm	580	202

Dimensions in mm, weights in kg. For a quote or advice on the right option for your truck, contact WOLFF Onsite at hello@wolffonsite.co.uk or call 01709 437141.

Specifications may change without notice. E&OE.