KITO

RED ROOSTER LIFTING

RAISING EXPECTATIONS

ED WIND HOIST

Single-phased KITO ED electric chain hoist is lightweight and robust as well as weatherproof and corrosion resistant.

STANDARD FEATURES

- 230 V / 50 Hz single-phase
- Hook suspension
- High-performance mechanical brake with friction clutch
- Range limit switch for lifting
- Single or dual lifting speed
- Weatherproof and corrosion resistant
- Aluminium gear casing

OPTIONS

- Radio remote control
- TMH plain trolley
- Foam hook protector

FOR YOUR WIND TURBINE	
LOAD CAPACITY	Up to 480 kg
OPERATING VOLTAGE	1 PH 230 V / 50 Hz
LIFTING HEIGHT	Up to 100 m, other lifting heights on request
LIFTING SPEED	Up to 20.1 m/min
CLASSIFICATION	FEM 1Am, ISO M4



LOAD CAPACITIES 60 KG TO 480 KG

480 kg capacity in double chain design, available with conversion set

HIGH-PERFORMANCE MECHANICAL BRAKE

With friction clutch

NICKEL-PLATED LOAD CHAIN

Grade T, series DAT (G80) in accordance with standard EN 818-7, Strength 800 N/mm2

HIGH LIFTING SPEED

max. 20.1 m/min





