TELEMETRY
LOAD CELL HANDSET

RED ROOSTER LIFTING

RAISING EXPECTATIONS

Information subject to change without notice
**Based on a BS1610 Grade 1 Calibration Machine*
***Depending on charge and conditions*



STANDARD FEATURES

- On/Off
- Tare
- Zero
- Peak hold
- Battery level indicator
- Frequency 433 MHz
- Eight digit display
- Select units in lbs, kg, tonne or US Tons
- Rubber cover with lanyard

AVAILABLE OPTIONS

- RS232C output for printer or data logging with Pipeline® software to PC or print mode
- AA Lithium batteries in handset for extended life
- Link supplied for use with rechargeable Lithium-Ion battery pack and charger
- Auto turn off on display
- Backlit display

TELEMETRY HANDSET	IKON-X
RESOLUTION	1 kg
ACCURACY	< +/- 0.5% of FSD*
TEMP RANGE	-10 °C to +40°C
HANDSET DIMENSIONS	245mm x 120mm x 50mm (524g)
HANDSET BATTERY	4 x "AA" Alkaline
BATTERY LIFE	(Alkaline "AA") Continuous Use: Minimum 50 Hours**
HANDSET DISPLAY	8 digit x 8mm

TELEMETRY
LOAD CELL HANDSET

RED ROOSTER LIFTING

RAISING EXPECTATIONS

