
TMH-20T-LHR
LOW HEADROOM AIR HOIST

RED ROOSTER LIFTING

RAISING EXPECTATIONS

The TMH-20T-LHR is a 20 tonne low headroom chain hoist and trolley from Red Rooster Lifting. This is part of our air hoist and trolley range for lifting equipment applications in industry.



The new **Red Rooster Lifting** TMH series air hoist and trolleys have the highest lifting speed with the lowest headroom on the hoist market. The TMH hoists are designed to operate at full lifting capacity with an air pressure from 4 – 6.3 bar. For full speed operation the hoist air pressure should be 6.3 bar.

STANDARD FEATURES

- Toku rotary vane motor
- Robust 3 step planetary gearbox
- Failsafe automatic internal disc brake
- Upper & lower limit switches
- Cast steel housing
- Internal silencing down to 80 dB(A)
- Alloy safety swivel hooks with safety catch
- Load chain of European manufacture EN818-7
- Automatic load limiter

AVAILABLE OPTIONS

- Marine specification
- Collision bumpers
- UK Ex scheme or ATEX zone 1 specification
- Articulated trolleys
- Rack & pinion drive
- Travel limits
- Air Service units
- Festoon systems
- Radio control remote
- Main air shut off valve
- Special paint systems
- Beam brake
- Other travel speeds

UK EX SCHEME ZONE 2
ATEX ZONE 2
AS STANDARD


TMH-20T-LHR
LOW HEADROOM AIR HOIST

RED ROOSTER LIFTING


RAISING EXPECTATIONS

DIMENSIONS

All measurements are in mm
Information subject to change without notice



MODEL	TMH-20T-LHR
WLL	20000 kg
CHAIN FALLS	4
LIFTING SPEED FULL LOAD (M/MIN)	0.8 m/min
LIFTING SPEED WITHOUT FULL LOAD	1.6 m/min
LOWERING SPEED FULL LOAD	1.6 m/min
TRAVEL SPEED	6.8 m/min
HOIST AIR CONSUMPTION	58 l/sec
TROLLEY AIR CONSUMPTION	40 l/sec
INLET CONNECTION	1" BSP
WEIGHT WITH 3M HOL	950 kg
ADDITIONAL METRE HOL	22.8 kg
FLANGE MINIMUM	130 mm
FLANGE MAXIMUM	300 mm
G.A. DRAWING	RRL 1597-00



-LHR = STANDARD *-LHR-ATX = ATEX*